


ADVANTAGE 22


Advantage 22 (2MADVE22) is a sturdy 22 oz. coated formula well equipped to handle adverse weather conditions and withstand great physical stress. Advantage 22 is well suited for truck tarp and oil boom applications. It's well designed construction allows it to remain flexible, even in cold temperatures, making it ideal for the long haul or use on water for oil spill containment.

2MADVE22	ENGLISH	METRIC	TESTING METHOD
Weight	22 oz./yd ²	745 g/m ²	FS 5040 / ASTM D3776
Stocked Widths	61" <i>capable up to 126"</i>	155 cm <i>capable up to 320 cm</i>	
Construction	15 x 15/1" by 1500 x 1500	6 x 6/cm by 1650 x 1650	
Grab Tensile	459 x 418 lbs./1"	2042 x 1859 N/2.5 cm	FS 5100 / ASTM D5034
Tongue Tear	140 x 150 lbs.	623 x 667 N	FS 5134 / ASTM D2261
Adhesion	22 lbs/2"	98 N/5 cm	FS 5970/ ASTM D751
Emboss/Finish	Matte		
Cold Crack	-30° F	-34° C	FS 5874 / ASTM D2136
Treatments	Anti-Mildew, UV		
Fire Retardant	Pass		Self-Extinguishing

PRODUCT USES AND APPLICATIONS



OIL BOOMS



TRUCK TARPS



877-716-6651 • INFO@VALUEVINYL.COM • VALUEVINYL.COM

The following information in regards to the chemical and physical properties of this product is based upon reliable testing methods. While reliable, these statistics are intended only as an informational source for your benefit and do not constitute a warranty and/or guarantee. The Purchaser is still required to determine if the product represented meets the individual needs of the Purchaser.