



ADVANTAGE MVP FR 18 RIPSTOP

- 18 oz. coated FR ripstop vinyl
- Available in 61", capable up to 126" width
- Anti-mildew treated, UV treated, passes FR 25.853 (a) & NFPA-701 FR tests
- Soft hand and smooth matte surface
- Double reinforced Ripstop thread

2FRMADVRS18

	IMPERIAL	METRIC	TESTING METHOD
Weight	18.5 oz/yd2	627 g/m2	FS 5040 / ASTM D3776
Stocked Widths	61" up to 126"	155 cm up to 320 cm	
Adhesion	29 x 24 lbs./2"	138 x 138 N/5cm	FS 5970 / ASTM D751
Cold Crack	-30° F	-34° C	FS 5874 / ASTM D2136
Grab Tensile	222 x 193 lbs./1"	1032 x 970 N/2.5 cm	FS 5100 / ASTM D5034
Tongue Tear	103 x 101 lbs.	667 x 525 N	FS 5134 / ASTM D2261
Fire Resistance	NFPA-701, FAR 25.853		
Emboss/Finish	Matte		
Treatments	Anti-Mildew, UV		
Applications	General Use, Specialty		

DESIGNED FOR
DURABILITY



(877) 716-6651 INFO@VALUEVINYLS.COM WWW.VALUEVINYLS.COM

The following information in regard to the chemical and physical properties of this product is based upon reliable testing methods. While reliable, these statistics are intended only as an informational source for your benefit and do not constitute a warranty and/or guarantee. The Purchaser is still required to determine if the product represented meets the individual needs of the Purchaser.

Rev. 2.2026



View Spec Sheet

ADVANTAGE MVP FR 18 RIPSTOP



Regal Blue