



CROSSCOURT SOLID WINDSCREEN 12

- 12 oz. laminated solid vinyl windscreen
- Available in 72", 96", 120", capable up to 126" width
- Anti-mildew treated, UV treated
- Smooth matte surface

3MBODY12

	IMPERIAL	METRIC	TESTING METHOD
Weight	12 oz/yd ²	407 g/m ²	FS 5040 / ASTM D3776
Stocked Widths	72", 96", 120" up to 126"	183 cm, 244 cm, 305 cm up to 320 cm	
Adhesion	24 lbs./2"	107 N/5cm	FS 5970 / ASTM D751
Cold Crack	-30° F	-34° C	FS 5874 / ASTM D2136
Grab Tensile	253 x 223 lbs./1"	1125 x 992 N/3 cm	FS 5100 / ASTM D5034
Tongue Tear	74 x 65 lbs./1"	329 x 289 N/3 cm	FS 5134 / ASTM D2261
Emboss/Finish	Matte		
Treatments	Anti-Mildew, UV		
Applications	Solid Windscreens		

DESIGNED FOR
SOLID WINDSCREENS



(877) 716-6651 INFO@VALUEVINYLS.COM WWW.VALUEVINYLS.COM

The following information in regard to the chemical and physical properties of this product is based upon reliable testing methods. While reliable, these statistics are intended only as an informational source for your benefit and do not constitute a warranty and/or guarantee. The Purchaser is still required to determine if the product represented meets the individual needs of the Purchaser.

Rev. 11.2025



View Spec Sheet

CROSSCOURT SOLID WINDSCREEN 12



Black

