



EXSCREEN 1717

- 7 oz. coated, extruded mesh
- Available in 126", capable up to 144" width
- Anti-mildew treated, UV treated
- Semi-Gloss finish

EXMIS55

	IMPERIAL	METRIC	TESTING METHOD
Weight	7 oz/yd2	238 g/m2	FS 5040 / ASTM D3776
Openness	45%		
Stocked Widths	36" up to 144"	91 cm up to 366 cm	
Grab Tensile	70 x 71 lbs./1"	311 x 316 N/2.5 cm	FS 5100 / ASTM D5034
Tongue Tear	30 x 33 lbs.	133 x 147 N	FS 5134 / ASTM D2261
Fire Retardant	Pass		California Tech, Bulletin 117 Sec E
Emboss/Finish	Semi-Gloss		
Treatments	Anti-Mildew, UV		
Applications	Exterior Insect Screens		

DESIGNED FOR
EXTERIOR INSECT SCREENS



(877) 716-6651 INFO@VALUEVINYLS.COM WWW.VALUEVINYLS.COM

The following information in regard to the chemical and physical properties of this product is based upon reliable testing methods. While reliable, these statistics are intended only as an informational source for your benefit and do not constitute a warranty and/or guarantee. The Purchaser is still required to determine if the product represented meets the individual needs of the Purchaser.

Rev. 07.2026



View Spec Sheet

EXSCREEN 1717



Black