



GTX-30

- 30 oz coated vinyl
- Available in 82", capable up to 126" width
- Anti-mildew treated, UV treated
- Smooth Matte surface

BGMEM30

	IMPERIAL	METRIC	TESTING METHOD
Weight	30 oz/yd ²	1017 g/m ²	FS 5040 / ASTM D3776
Stocked Widths	61" up to 82"	155 cm up to 208 cm	
Adhesion	40 lbs./2"	178 N/5cm	FS 5970 / ASTM D751
Cold Crack	-35° F	-37° C	FS 5874 / ASTM D2136
Grab Tensile	585 x 635 lbs./1"	2602 x 2825 N/2.5 cm	FS 5100 / ASTM D5034
Trapezoid Tear	78 x 71 lbs./1"	347 x 316 N/2.5 cm	FS 5136 / ASTM D4533
Abrasion	7000 cycles		FS 5306 / ASTM D3884
Emboss/Finish	Matte		
Treatments	Anti-Mildew, UV		
Applications	Geosynthetics, Landfill and Pond liners, Containment, Oil storage		

DESIGNED FOR
CHEMICAL RESISTANCE



(877) 716-6651 INFO@VALUEVINYL.COM WWW.VALUEVINYL.COM


The following information in regard to the chemical and physical properties of this product is based upon reliable testing methods. While reliable, these statistics are intended only as an informational source for your benefit and do not constitute a warranty and/or guarantee. The Purchaser is still required to determine if the product represented meets the individual needs of the Purchaser.

Rev. 2.2026



View Spec Sheet

GTX-30



Black