



SOLUNA 19

- 19 oz. coated fabric for outdoor fixed awning and wall pad applications
- Limitless digital print shelf life for sharp, vibrant prints
- Woven construction for superior tensile, tear, and puncture strength
- Colors stay true batch-to-batch
- Antifungal, anti-mildew, anti-mold and UV additives
- High-performance UV additives for superior outdoor life and color fastness
- 5-year pro-rated warranty for peace of mind
- Orange-peel emboss that looks good day or night

JCALFR1961

	IMPERIAL	METRIC	TESTING METHOD
Weight	19 oz/yd ²	650 g/m ²	FS 5040 / ASTM D3776
Stocked Widths	61" up to 80"	155 cm up to 203 cm	
Adhesion	38 lbs./2"	169 N/5cm	FS 5970 / ASTM D751
Cold Crack	-30° F	-34° C	FS 5874 / ASTM D2136
Grab Tensile	750 x 655 lbs./1"	3336 x 2914 N/5 cm	FS 5100 / ASTM D5034
Tongue Tear	153 x 135 lbs.	681 x 601 N	FS 5134 / ASTM D2261
Emboss/Finish	Matte Printable; Orange-Peel Emboss, Low Sheen		
Fire Retardant	PASS		ASTM E84, NFPA-701
Treatments	High UV, BACshield: Antimicrobial, Anti-Mildew, Anti-Mold, Antibacterial		
Applications	Outdoor Fixed Awning, Window Topping, Shade Control, and Outdoor Wallpadding.		

DESIGNED FOR
OUTDOOR APPLICATIONS



(877) 716-6651 INFO@VALUEVINYL.COM WWW.VALUEVINYL.COM

The following information in regard to the chemical and physical properties of this product is based upon reliable testing methods. While reliable, these statistics are intended only as an informational source for your benefit and do not constitute a warranty and/or guarantee. The Purchaser is still required to determine if the product represented meets the individual needs of the Purchaser.

Rev. 08.2026



Download
Spec Sheet

SOLUNA 19



Burgundy



Black Navy Royal Blue Blue



Red Forest Green Emerald English Brown *



Sunflower Sand Beige Grey White

* Call for availability and minimum order quantities.