



STRUCTURETEC BLOCKOUT 22 OZ.

- 22 oz. coated blackout
- Stocked in 61" capable up to 126" inches
- Anti-mildew treated, UV treated, passes NFPA-701 FR test
- Acrylic lacquer topcoat on both sides

JSTBO22

structuretec

	IMPERIAL	METRIC	TESTING METHOD
Weight	22 oz/yd ²	745 g/m ²	FS 5040 / ASTM D3776
Stocked Widths	98" up to 126"	250 cm up to 320 cm	
Adhesion	20 x 19 lbs./2"	89 x 85 N/5cm	FS 5970 / ASTM D751
Cold Crack	-30° F	-34° C	FS 5874 / ASTM D2136
Grab Tensile	175 x 151 lbs./1"	778 x 672 N/2.5 cm	FS 5100 / ASTM D5034
Tongue Tear	55 x 63 lbs./1"	245 x 280 N/2.5 cm	FS 5134 / ASTM D2261
Abrasion	2500 cycles		FS 5306 / ASTM D3884
Emboss/Finish	Acrylic Laquer 1/1		
Treatments	Anti-Mildew, UV, Blackout		
Fire Retardant	Pass		NFPA-701
Applications	Event Tents, Structure Fabrics, Tensile Structures		

DESIGNED FOR
TENT STRUCTURES



(877) 716-6651 INFO@VALUEVINYL.COM WWW.VALUEVINYL.COM


The following information in regard to the chemical and physical properties of this product is based upon reliable testing methods. While reliable, these statistics are intended only as an informational source for your benefit and do not constitute a warranty and/or guarantee. The Purchaser is still required to determine if the product represented meets the individual needs of the Purchaser.

Rev. 11.2025



View Spec Sheet

STRUCTURETEC BLOCKOUT 22 OZ.



White