



STRUCTURETEC 18

- 18 oz. coated PVC
- Stocked in 61" capable up to 126" width
- Anti-mildew treated, UV treated, passes NFPA-701 FR test
- Acrylic Lacquer topcoat on the face for easy maintenance

XADVFRGAL18

structuretec

	IMPERIAL	METRIC	TESTING METHOD
Weight	18.5 oz/yd ²	627 g/m ²	FS 5040 / ASTM D3776
Stocked Widths	61" up to 126"	155 cm up to 320 cm	
Adhesion	46 x 34 lbs./2"	205 x 151 N/5cm	FS 5970 / ASTM D751
Cold Crack	-30° F	-34° C	FS 5874 / ASTM D2136
Grab Tensile	148 x 145 lbs./1"	658 x 645 N/2.5 cm	FS 5100 / ASTM D5034
Tongue Tear	72 x 70 lbs./1"	320 x 311 N/2.5 cm	FS 5134 / ASTM D2261
Abrasion	2500 cycles		FS 5306 / ASTM D3884
Emboss/Finish	Acrylic Laquer 1/0 - Gloss		
Treatments	Anti-Mildew, UV		
Fire Retardant	Pass		NFPA-701
Applications	Event Tents, Structure Fabrics, Tensile Structures		

DESIGNED FOR
TENT STRUCTURES



(877) 716-6651 INFO@VALUEVINYL.COM WWW.VALUEVINYL.COM


The following information in regard to the chemical and physical properties of this product is based upon reliable testing methods. While reliable, these statistics are intended only as an informational source for your benefit and do not constitute a warranty and/or guarantee. The Purchaser is still required to determine if the product represented meets the individual needs of the Purchaser.

Rev. 4.2026



View Spec Sheet

STRUCTURETEC 18



White