



SURESEAL EXTREME 45

- 45 oz. coated vinyl
- Available in 61" width
- Anti-mildew treated, UV treated
- Sand grain surface
- Full Panama base fabric
- High tear strength and puncture resistant

BSURX45

	IMPERIAL	METRIC	TESTING METHOD
Weight	45 oz/yd ²	1526 g/m ²	FS 5040 / ASTM D3776
Stocked Widths	61" up to 80"	145 cm up to 203 cm	
Adhesion	81 x 78 lbs./2"	182 x 182 N/5cm	FS 5970 / ASTM D751
Cold Crack	-40° F	-40° C	FS 5874 / ASTM D2136
Grab Tensile	403 x 425 lbs./1"	1793 x 1890 N/2.5 cm	FS 5100 / ASTM D5034
Tongue Tear	145 x 164 lbs./1"	498 x 525 N/2.5 cm	FS 5134 / ASTM D2261
Abrasion	65,000 cycles		FS 5306 / ASTM D3884
Puncture	261		ASTM D751
Emboss/Finish	Sand grain		
Treatments	Anti-Mildew, UV		
Applications	Dock seal, Dock shelters, Wear pleats		

DESIGNED FOR
DOCK SEALS



(877) 716-6651 INFO@VALUEVINYL.COM WWW.VALUEVINYL.COM


The following information in regard to the chemical and physical properties of this product is based upon reliable testing methods. While reliable, these statistics are intended only as an informational source for your benefit and do not constitute a warranty and/or guarantee. The Purchaser is still required to determine if the product represented meets the individual needs of the Purchaser.

Rev. 09.15.2025



View Spec Sheet

SURESEAL EXTREME 45



Black