



SURESEAL RIP-STOP LACQUERED 17

- 17 oz. coated vinyl
- Available in 61" width
- Anti-mildew treated, UV treated
- Gloss Acrylic Lacquer topcoat
- Used for inflatable extension dock shelters
- Increased tear strength

BADVRSAL17

	IMPERIAL	METRIC	TESTING METHOD
Weight	17 oz/yd ²	576 g/m ²	FS 5040 / ASTM D3776
Stocked Widths	61" up to 80"	155 cm up to 203 cm	
Adhesion	9 x 9 lbs./2"	40 x 40 N/5cm	FS 5970 / ASTM D751
Cold Crack	-40° F	-40° C	FS 5874 / ASTM D2136
Strip Tensile	280 x 325 lbs./1"	1246 x 1446 N/2.5 cm	FS 5100 / ASTM D5034
Tongue Tear	68 x 50 lbs./1"	302 x 222 N/2.5 cm	FS 5134 / ASTM D2261
Emboss/Finish	Acrylic Lacquer 1/0 - Gloss		
Treatments	Anti-Mildew, UV		
Applications	Dock seal, Transportation		

DESIGNED FOR
DOCK SEALS



(877) 716-6651 INFO@VALUEVINYLS.COM WWW.VALUEVINYLS.COM


The following information in regard to the chemical and physical properties of this product is based upon reliable testing methods. While reliable, these statistics are intended only as an informational source for your benefit and do not constitute a warranty and/or guarantee. The Purchaser is still required to determine if the product represented meets the individual needs of the Purchaser.

Rev. 09.15.2025



View Spec Sheet

SURESEAL RIP-STOP LACQUERED 17



Black



Blue