



SURESEAL 35

- 35 oz. coated vinyl
- Available in 61" width
- Anti-mildew treated, UV treated
- Smooth matte surface
- Resists tears and abrasion
- Tough, resilient, and sturdy

BSUR35

	IMPERIAL	METRIC	TESTING METHOD
Weight	35 oz/yd ²	1186 g/m ²	FS 5040 / ASTM D3776
Stocked Widths	61" up to 80"	155 cm up to 203 cm	
Adhesion	40 x 40 lbs./2"	178 x 178 N/5cm	FS 5970 / ASTM D751
Cold Crack	-40° F	-40° C	FS 5874 / ASTM D2136
Grab Tensile	257 x 246 lbs./1"	1143 x 1094 N/2.5 cm	FS 5100 / ASTM D5034
Tongue Tear	193 x 181 lbs.	859 x 805 N	FS 5134 / ASTM D2261
Abrasion	18000 cycles		FS 5306 / ASTM D3884
Emboss/Finish	Matte		
Treatments	Anti-Mildew, UV		
Applications	Dock seal, Dock shelters, Wear pleats		

DESIGNED FOR
DOCK SEALS



(877) 716-6651 INFO@VALUEVINYL.COM WWW.VALUEVINYL.COM


The following information in regard to the chemical and physical properties of this product is based upon reliable testing methods. While reliable, these statistics are intended only as an informational source for your benefit and do not constitute a warranty and/or guarantee. The Purchaser is still required to determine if the product represented meets the individual needs of the Purchaser.

Rev. 11.2025



View Spec Sheet

SURESEAL 35



Black