



VOLAR 10

- 10 oz. coated vinyl
- Available in 61", capable up to 126" width
- Anti-mildew treated, UV treated, passes NFPA-701 FR test
- Smooth Gloss surface

2XCAIG10

	IMPERIAL	METRIC	TESTING METHOD
Weight	10 oz/yd ²	322 g/m ²	FS 5040 / ASTM D3776
Stocked Widths	61" up to 126"	155 cm up to 320 cm	
Adhesion	19 x 18 lbs./2"	85 x 80 N/5cm	FS 5970 / ASTM D751
Cold Crack	-22° F	-30° C	FS 5874 / ASTM D2136
Grab Tensile	102 x 101 lbs./1"	454 x 449 N/2.5 cm	FS 5100 / ASTM D5034
Tongue Tear	34 x 40 lbs./1"	151 x 178 N/2.5 cm	FS 5134 / ASTM D2261
Fire Retardant	Pass		NFPA-701
Emboss/Finish	Gloss		
Treatments	UV, Anti-Mildew		
Applications	Cold Air Inflatables, Specialty		

DESIGNED FOR
COLD AIR INFLATABLES



(877) 716-6651 INFO@VALUEVINYLS.COM WWW.VALUEVINYLS.COM

The following information in regard to the chemical and physical properties of this product is based upon reliable testing methods. While reliable, these statistics are intended only as an informational source for your benefit and do not constitute a warranty and/or guarantee. The Purchaser is still required to determine if the product represented meets the individual needs of the Purchaser.

Rev. 12.2025



View Spec Sheet

VOLAR 10



Grey



Black



White