



X-MESH 12

- 12 oz. extrusion coated mesh
- Available in a 54", capable up to 120" width
- Anti-mildew treated, UV treated
- Smooth Matte surface

MXM12

	IMPERIAL	METRIC	TESTING METHOD
Weight	12 oz/yd2	407 g/m2	FS 5040 / ASTM D3776
Openness	55%		
Stocked Widths	54" up to 120"	137 cm up to 305 cm	
Cold Crack	-30° F	-34° C	FS 5874 / ASTM D2136
Grab Tensile	350 lbs./2"	1557 N/5 cm	FS 5100 / ASTM D5034
Tongue Tear	60 lbs.	267 N	FS 5134 / ASTM D2261
Emboss/Finish	Matte		
Treatments	Anti-Mildew, UV		
Applications	Underside of Marine Boat Cushions, Other General Use, Specialized Industrial Usage		

DESIGNED FOR
GENERAL USE



(877) 716-6651 INFO@VALUEVINYLS.COM WWW.VALUEVINYLS.COM

The following information in regard to the chemical and physical properties of this product is based upon reliable testing methods. While reliable, these statistics are intended only as an informational source for your benefit and do not constitute a warranty and/or guarantee. The Purchaser is still required to determine if the product represented meets the individual needs of the Purchaser.



View Spec Sheet

X-MESH 12



Black



White